

Wölb 0

SP [m]	HL EWD [°]	Flg EWD [°]	Anstellwinkel	Ca	Stabilität
0,108	0	2	1,334	0,604	15,292
0,108	0	2,1	1,456	0,625	15,291
0,108	0	2,2	1,577	0,645	15,289
0,108	0	2,3	1,699	0,665	15,287
0,108	0	2,4	1,820	0,686	15,284
0,108	0	2,5	1,942	0,706	15,281
0,108	0	2,6	2,063	0,727	15,278
0,108	0	2,7	2,184	0,747	15,275

Wölb 0

Geschwindigkeit	Gleitzahl E	Steigzahl	Sinkgeschw.
12,452	22,336	17,356	0,558
12,246	22,619	17,871	0,541
12,050	22,750	18,267	0,530
11,864	22,936	18,705	0,517
11,686	23,133	19,153	0,505
11,516	23,248	19,533	0,495
11,354	23,428	19,966	0,485
11,198	23,587	20,381	0,475

			Wölbung		
Wölbung	EWD	Anstellwinkel	Ca	Stabilität	Geschwindigkeit
6,3 / 6,3	2,4	2,29	0,98	15,07	9,76

Wölbung

Gleitzahl E	Steigzahl	Sinkgeschw.
25,6	25,39	0,38