

GRUNDIERWACHS

Beschreibung

- **Hochwirksame Wachsgrundierung für schlecht benetzbare Untergründe.**
- **Siliconfrei**

Verarbeitung

In Siliconformen wird Grundierwachs alleine, in **GFK-Formen** in Verbindung **mit Folientrennmittel PVA** eingesetzt. PVA trocknet auf dieser Grundierung ohne die manchmal auftretenden Fehlstellen (Augen und Pinselftriche).

Das Grundierwachs wird mit einem weichen Baumwolltuch (an schlecht zugänglichen Stellen mit einem Pinsel) dünn und gleichmäßig aufgetragen.

Eine Glanzpolitur ist nicht möglich und auch nicht erforderlich, da das nachfolgende Folientrennmittel hochglänzend aufdrocknet.

Lagerung

In ungeöffneten Originalgebinden ca. 6 Monate.

Packungsgrößen von 0,25 - 10 Liter
Bestell-Nr. 165 115-X

PRIMING WAX

Description

- **Highly efficient priming wax for base surfaces with low wetting properties.**
- **Silicone-free.**

Processing

Priming wax is used alone in silicone moulds and combined **with film release agent PVA in GRP moulds**. PVA dries on this priming coat without giving rise to the voids that sometimes occur (bubbles or brush marks).

A thin and uniform coat of priming wax is applied with a soft cotton cloth (or a brush at sites difficult to access). Polishing to a gloss is neither possible nor required: the following film release agent dries to form a high-gloss surface.

Storage

Approx. six months in the unopened original packaging.

Packaging sizes from 0.25 to 10 l
Order no. 165 115-X



Triathlon-Fahrrad aus Kohlefaser/Epoxydharz
(Karl Bodenhöfer, Waltenhofen)

Triathlon bicycle of carbon-fibre reinforced epoxy resin
(Karl Bodenhöfer, Waltenhofen)